

# **SELF DRILL PLUG WITH SCREW - ZAMAK**





## **FEATURES**

Material: Zamak


#### Advantages:


- · Quick setting without drilling.
- Zamak, high heat resistance material.
- Use on plasterboard 10 to 20 mm thickness.


## **APPLICATION EXAMPLES**

- Heat
- · Ventilation and conditioned air
- Material and electrical accessories
- · Material and plumbing accessories
- Wall-mounted lamp
- TV
- Shelves
- Decoration

#### **INSTALLATION**








Insert the screw in the center of the plug and then, tight through the fixing piece

# **RECOMMENDED LOADS**

Loads are calculated from tests done on the production site and a partial coefficient action = 4.

Material	<del>=</del> Tension	<b>√¬:</b> Shear
	daN	daN
Plasterboard 13mm	10	10

#### **INSTALLATION DATA**



Item code	Plug length	Screw length	Screw diameter	Wall thickness	Fasten Up to	Qty Per Box	Qty per outer	Weight Per 100
	L	Lvis	Øvis	EP	tfix			
	mm	mm	mm	Min-Max. mm	mm			kg
Countersun	k head scre	W						
SDPZ-C	31	35	4.5	10-20	15	100	800	0.75
Cylindrical	head screw							
SDPZ-P	31	35	4.5	10-20	15	200	800	0.65