

Sheet Metal Working Screw
Steel Pan Head Square Drive



Diameter	Length	Shear	Tensile	Material depth	Drill capacity for steel	Wrench	Max Speed	Socket	Reference
3.5	10	2930	5000	4	2.0	2800		SQ1	TCQ35010
3.5	13	2930	5000	7	2.0	2800		SQ1	TCQ35013
3.5	16	2930	5000	10	2.0	2800		SQ1	TCQ35016
3.5	19	2930	5000	8	2.0	2800		SQ1	TCQ35019
3.9	13	3650	6000	7	2.5	3800		SQ2	TCQ39013
3.9	16	3650	6000	10	2.5	3800		SQ2	TCQ39016
3.9	19	3650	6000	8	2.5	3800		SQ2	TCQ39019
3.9	25	3650	6000	19	2.5	3800		SQ2	TCQ39025
3.9	32	3650	6000	26	2.5	3800		SQ2	TCQ39032
3.9	38	3650	6000	32	2.5	3800		SQ2	TCQ39038
4.2	13	4360	7000	6	3.0	4800		SQ2	TCQ42013
4.2	16	4360	7000	9	3.0	4800		SQ2	TCQ42016
4.2	19								TCQ42019
4.2	25	4360	7000	18	3.0	4800		SQ2	TCQ42025
4.2	32	4360	7000	25	3.0	4800		SQ2	TCQ42032
4.2	38	4360	7000	31	3.0	4800		SQ2	TCQ42038
4.2	50	4360	7000	43	3.0	4800		SQ2	TCQ42050
4.8	13	6280	10000	4	4.0	7000	2000	SQ2	TCQ48013
4.8	16	6280	10000	7	4.0	7000	2000	SQ2	TCQ48016
4.8	19	6280	10000	10	4.0	7000	2000	SQ2	TCQ48019
4.8	25	6280	10000	16	4.0	7000	2000	SQ2	TCQ48025
4.8	32	6280	10000	23	4.0	7000	2000	SQ2	TCQ48032
4.8	38	6280	10000	29	4.0	7000	2000	SQ2	TCQ48038
4.8	45	6280	10000	36	4.0	7000	2000	SQ2	TCQ48045
4.8	50	6280	10000	41	4.0	7000	2000	SQ2	TCQ48050
4.8	60	6280	10000	51	4.0	7000	2000	SQ2	TCQ48060
4.8	70	6280	10000	61	4.0	7000	2000	SQ2	TCQ48070
4.8	80	6280	10000	71	4.0	7000	2000	SQ2	TCQ48080
5.5	19	8360	12500	9	5.0	10500	1750	SQ3	TCQ55019
5.5	25	8360	12500	15	5.0	10500	1750	SQ3	TCQ55025