

Sheet Metal Working Screw

Screw, Torx Drive Countersunk Head - Zinc Plated

Ø	length	Shear	Tensile	G	Drill capacity for steel	Socket	Référence
Diamètre							
3.5	13	3650	6000	7	2,25	TX15	TFX35013
	16	3650	6000	10	2,25	TX15	TFX35016
	19	3650	6000	13	2,25	TX15	TFX35019
	22	3650	6000	16	2,25	TX15	TFX35022
	25	3650	6000	19	2,25	TX15	TFX35025
3.9	16	3650	6000	10	2,4	T20	TFX39016
	19	3650	6000	13	2,4	T20	TFX39019
	22	3650	6000	16	2,4	T20	TFX39022
	25	3650	6000	19	2,4	T20	TFX39025
	32	3650	6000	26	2,4	T20	TFX39032
4.2	16	3650	6000	9	3	T20	TFX42016
	19	3650	6000	12	3	T20	TFX42019
	22	3650	6000	15	3	T20	TFX42022
	25	3650	6000	18	3	T20	TFX42025
	32	3650	6000	25	3	T20	TFX42032
4.8	38	3650	6000	31	3	T20	TFX42038
	16	3650	6000	7	4,4	T25	TFX48016
	19	3650	6000	10	4,4	T25	TFX48019
	22	3650	6000	13	4,4	T25	TFX48022
	25	3650	6000	16	4,4	T25	TFX48025
	32	3650	6000	23	4,4	T25	TFX48032
	38	3650	6000	29	4,4	T25	TFX48038
5.5		3650	6000	36	4,4	T25	TFX48045
		3650	6000	41	4,4	T25	TFX48050
	25	3650	6000	15	5,25	T25	TFX55025
	32	3650	6000	22	5,25	T25	TFX55032
	38	3650	6000	28	5,25	T25	TFX55038
6.3		3650	6000	35	5,25	T25	TFX55045
		3650	6000	40	5,25	T25	TFX55050
		3650	6000	57	6	T30	TFX63070