

## Sheet Metal Working Screw

**BRIGHT ZINC-PLATED STEEL,  
HEXAGONAL-HEADED,  
BONDED EPDM WASHER**


Diameter	Length	Shear	Tensile	Material depth	Drill capacity for steel	Wrench	Max Speed	Socket	Reference
4.8	16	6280	10000	7	4.0	7000	2000	8.0	THR14-48016
4.8	19	6280	10000	10	4.0	7000	2000	8.0	THR14-48019
4.8	25	6280	10000	16	4.0	7000	2000	8.0	THR14-48025
4.8	32	6280	10000	23	4.0	7000	2000	8.0	THR14-48032
4.8	38	6280	10000	28	4.0	7000	2000	8.0	THR14-48038
5.5	19	8360	12500	9	5.0	10500	1750	8.0	THR16-55019
5.5	25	8360	12500	15	5.0	10500	1750	8.0	THR16-55025
5.5	32	8360	12500	22	5.0	10500	1750	8.0	THR16-55032
5.5	38	8360	12500	28	5.0	10500	1750	8.0	THR16-55038
5.5	75	8360	12500	65	5.0	10500	1750	8.0	THR16-55075
6.3	25	12270	17000	14	6.0	17000	1500	5.0	THR16-63025
6.3	32	12270	17000	21	6.0	17000	1500	5.0	THR16-63032
6.3	38	12270	17000	27	6.0	17000	1500	5.0	THR16-63038
6.3	45	12270	17000	34	6.0	17000	1500	5.0	THR16-63045
6.3	50	12270	17000	39	6.0	17000	1500	5.0	THR16-63050
6.3	63	12270	17000	52	6.0	17000	1500	5.0	THR16-63063
6.3	75	12270	17000	64	6.0	17000	1500	5.0	THR16-63075
6.3	100	12270	17000	89	6.0	17000	1500	5.0	THR16-63100